

Breathe before Speaking: Efficient Information Dissemination Despite Noisy, Limited and Anonymous Communication

Ofer Feinerman*
Weizmann Institute
Rehovot, Israel
ofer.feinerman@weizmann.ac.il

Bernhard Haeupler
Microsoft Research
Mountain View, CA 94043, USA
haeupler@cs.cmu.edu

Amos Korman†
CNRS and Univ. Paris Diderot
Paris, 75013, France
amos.korman@liafa.univ-paris-diderot.fr

Abstract

Distributed computing models typically assume reliable communication between processors. While such assumptions often hold for engineered networks, e.g., due to underlying error correction protocols, their relevance to biological systems, wherein messages are often distorted before reaching their destination, is quite limited. In this study we aim at bridging this gap by rigorously analyzing a model of communication in large anonymous populations composed of simple agents which interact through short and highly unreliable messages.

We focus on the rumor-spreading problem and the majority-consensus problem, two fundamental tasks in distributed computing, and initiate their study under communication noise. Our model for communication is extremely weak and follows the push gossip communication paradigm: In each synchronous round each agent that wishes to send information delivers a message to a random anonymous agent. This communication is further restricted to contain only one bit (essentially representing an opinion). Lastly, the system is assumed to be so noisy that the bit in each message sent is flipped independently with probability $1/2 - \epsilon$, for some small $\epsilon > 0$.

Even in this severely restricted, stochastic and noisy setting we give natural protocols that solve the noisy rumor-spreading and the noisy majority-consensus problems efficiently. Our protocols run in $O(\log n/\epsilon^2)$ rounds and use $O(n \log n/\epsilon^2)$ messages/bits in total, where n is the number of agents. These bounds are asymptotically optimal and, in fact, are as fast and message efficient as if each agent would have been simultaneously informed directly by the source. Our efficient, robust, and simple algorithms suggest balancing between silence and transmission, synchronization, and majority-based decisions as important ingredients towards understanding collective communication schemes in anonymous and noisy populations.

1 Introduction

1.1 Background and Motivation

Information theory originated as a search for methods to manage communication noise in engineered systems [49]. In many ways, this search has reached its goals. The existence of coding methods that reduce error rates to practically zero were proven to exist [49]. Not less important, such codes have been realized in

*Incumbent of the Shlomo and Michla Tomarin Career Development Chair. Supported by the Clore Foundation, the Israel Science Foundation (FIRST grant no. 1694/10), and the Minerva Foundation.

†Supported in part by the ANR project DISPLEXITY, and by the INRIA project GANG.

a myriad of real-world systems [44]. In other words, given a large enough bandwidth, one can encode a message with a large number of error correcting bits in a way that makes communication noise essentially a non-issue. Fault-tolerance study in distributed computing focuses either on weak faults such as node *crashes* and message *failures*, or on very strong faults modeled as adversarial (*Byzantine*) interventions, but messages that are transmitted from one processor are, typically, assumed to reach their destination without distortion. Indeed, this perfect transmission relies on an implicit assumption that error-correcting is guaranteed by a lower level protocol that is responsible for implementing communication.

In contrast, communication in the natural world is inherently noisy. Biology, for one, is replete with communicating ensembles on all levels of organization: from molecules (e.g., the immune complement system [14]), and cells (e.g., bacterial populations [8]) to societies (e.g., a superorganism of social insects [52]). Whereas it is unrealistic to assume adversarial interventions, biological signals are extremely vulnerable to random distortion as they are being generated (e.g., probabilistic vesicle release in neuronal synapses [3]), transmitted over noisy media (e.g., acoustic communication in noisy environments [13]) and received (e.g., non-reliable measurements taken by immune cells [22].) Nevertheless, many studies show that, in practice, biological ensembles function reliably despite communication noise [23,47].

How biological systems overcome communication noise is a very basic and intriguing question. Indeed, for systems composed of simple and restricted individuals, as is often the case in biology, it may not be reasonable to assume sophisticated error-correcting at the level of an individual channel. Furthermore, when message size is highly restricted, redundancy drastically reduces the available alphabet and hence could not be used extensively. On the other hand, with only little redundancy, a random fault in the content of a transmitted message may lead to the reception of a meaningful message that is inconsistent with the original one [38].

1.2 Context and related work

Our paper falls within the scope of natural algorithms, a recent attempt to investigate biological phenomena from an algorithmic perspective [1, 11, 16, 39]. Within this framework, many works in the computer science discipline have studied different computational aspects of abstract systems composed of simple and restrict individuals. This includes, in particular, the study of *population protocols* [4, 5, 7, 10, 40], which considers constant size individuals interacting in pairs (using constant size messages) in a communication pattern which is either uniformly at random or adversarial, and the *beeping* model [1, 2, 21], which assumes a fixed network with extremely restricted communication. However, despite interesting results obtained in such models, the understanding of their fault-tolerance aspects is still lacking [5, 10]. Here, we study basic distributed tasks in a model that includes highly restricted *and* noisy communication.

Disseminating information to all the nodes of a network is one of the most fundamental communication primitives. In particular, the *rumor-spreading* problem, where a single piece of information initially residing at some source node is to be disseminated, and variants of it have received a lot of attention in the literature, see, e.g., [15, 17, 19, 24, 28–32, 36]. Much of this research was devoted to bounding measures such as the number of rounds, and the total number of messages. Fault tolerant rumor-spreading algorithms have also been studied extensively, especially in complete networks and in synchronous environments, where the focus has been on weak types of failures such as (probabilistic) message failures and initial node crashes. Essentially, it has been shown that there exist rumor-spreading protocols that can overcome such faults with a relatively little penalty [18–20, 30, 33, 36]. In the *majority-consensus* problem processors are required to agree on a common output value which is the majority input value [6, 9]. In general, this problem has been studied under similar models to the ones used for studying the rumor-spreading problem, but, in comparison to the latter problem, has received much less attention in the literature.

Rumor-spreading related problems were studied in other contexts as well, often with settings where communication noise is inherent. Network information theory [27] discusses the problem of disseminating information from one or more sources to a large number of recipients over noisy information channels. The settings there are, however, different from those that interest us as they are non-distributed in nature and allow for complex coding schemes that may be computationally complex for simple agents [37]. Engineers have studied the related problem of sensor network consensus formation in the presence of communication noise and have demonstrated, for example, tradeoffs between consensus quality and running time [35]. Physicists have studied the spreading of epidemics [41] and the formation of consensus around a zealot in voter mod-

els [42, 43] within probabilistic settings that include communication noise. These physically inspired studies often assume very simple algorithms and analyze their performance - this is different from a computer science approach which focuses on identifying the most efficient algorithms. Indeed, rumor spreading within a noisy voter model setting is expected to yield long convergence times, polynomial in the number agents.

Examples in biology: In the biological world, rumor-spreading is a common phenomenon which allows, for example, that a single receptor activate an entire cell [51], a small number of cells trigger large population responses [23], or a small number of vigilant individuals alert their herd [48]. There have been several direct experimental demonstrations of reliable rumor-spreading using unreliable messaging in biological systems. Examples include knowledgeable ants informing their nestmates regarding available food [47] and precise temporal codes achieved by coordinated neuronal populations [34]. Such examples serve as motivation for a more thorough theoretical understanding of how rumors spread through groups of simple individuals that communicate by noisy messages. Majority-consensus problems have also been shown to be relevant for several biological systems: Ants choosing between two alternative nesting sites and reach consensus on a nest that attracts a larger number of scouts [25] and a group of fish that reach consensus around the larger group of leaders [50] being two examples.

1.3 Model and Problems

1.3.1 Problem Definitions

As a first step into the study of noisy information dissemination, we study a very simple scenario in which there are only two possible states (or *opinions*) for the environment, namely, 0 and 1, one of which is the *correct* opinion, denoted by \mathcal{B} . We study two information dissemination problems both of which consider of n anonymous *agents*.

In the *noisy rumor-spreading* problem, we start the execution with one designated agent, called the *source* (representing the environment) that holds the correct opinion \mathcal{B} , while all other $n - 1$ agents initially have no information regarding \mathcal{B} . Agents can propagate information and update their knowledge by using (noisy) interactions as specified below. The goal is that eventually, *with high probability*, all agents adopt \mathcal{B} as their final opinion. Throughout we denote with high probability any probability of at least $1 - 1/n^c$, for some sufficiently large constant $c > 2$.

In the *noisy majority-consensus* problem, we consider that initially we have a subset A of agents, each of which having an opinion in $\{0, 1\}$ (all other agents do not have an opinion), where \mathcal{B} is the majority opinion among the agents in A . The problem is parameterized by the extent to which \mathcal{B} is more common. That is, the *majority-bias* of A is defined as $\frac{1}{2}(A_{\mathcal{B}} - A_{\bar{\mathcal{B}}})/|A|$, where A_i is the number of agents in the initial opinionated group, A , with opinion i , for $i \in \{0, 1\}$. As in the noisy rumor-spreading problem, the goal of the agents is to guarantee that with high probability, at the end of the execution, all agents hold the opinion \mathcal{B} .

1.3.2 The *Flip* model of communication

We assume a *synchronous* setting, in which all agents start the execution simultaneously and communication takes place in discrete rounds [45]. As mentioned, agents can use their (noisy) interactions to inform and update their opinion. In each round, each agent can choose to *wait*, i.e, do nothing, or to *send* a message.

The interaction pattern we study follows the standard *push* gossip model [17, 36, 46], where in each round each agent that chooses to send a message sends this message to another agent, chosen uniformly at random, without sender or receiver learning about each other's identity. If an agent receives several messages at the same round, it can only accept one of them (chosen uniformly at random), and all other messages are dropped. The message size is extremely restricted, specifically, each message sent consists of a single bit essentially encoding an opinion. Let $\epsilon > 0$ be a parameter. All messages are subject to noise, specifically, for each message sent by an agent, upon receiving it, the bit in the message is *flipped* independently with probability at most $1/2 - \epsilon$.

1.3.3 Symmetric algorithms

We view the two possible opinions $\{0, 1\}$ as abstract symmetric opinions that cannot affect any decision made by individual agents, except for which message to transmit¹. Accordingly, we consider only *symmetric* algorithms, in which the choices of individuals of whether or not to send a message at a given time are oblivious of the value of \mathcal{B} . That is, when fixing all random bits involved in an execution, the message-pattern (i.e., who sends who and at what time) in symmetric algorithms is the same regardless of whether \mathcal{B} equals 1 or 0.

1.4 Lower Bounds

The restriction of the symmetric noisy rumor-spreading problem (or the majority-consensus problem) to two parties is, in some sense, classical for the area of information theory. Here, a source agent a wishes to deliver its bit opinion \mathcal{B} to the second agent b through a binary symmetric channel with crossover probability $p = 1/2 - \epsilon$. The seminal result by Shannon [49] implies that using the channel $\Theta(1/\epsilon^2)$ times is both necessary and sufficient, for allowing b to possess the opinion \mathcal{B} with sufficiently high constant probability. This immediately implies a $\Theta(1/\epsilon^2)$ bound for the number of rounds needed for the same confidence guarantee in the two-party noisy rumor-spreading problem, since each message here contains precisely one bit. When it comes to a population of n agents, the goal is to have each agent possess the opinion \mathcal{B} with high probability (at least $1 - 1/n^c$). In this case, each agent would individually need to obtain $\Omega(\frac{1}{\epsilon^2} \log n)$ messages, even if all messages would come directly from the source node. These bounds immediately imply a lower bound of $\Omega(\frac{1}{\epsilon^2} n \log n)$ on the total bit complexity and hence also on the total number of messages sent. Moreover, since we assume that an agent can handle at most one message at a time, we get that $\Omega(\frac{1}{\epsilon^2} \log n)$ is also a lower bound on the number of rounds. All these bounds apply even if all messages would be as informative as those originated by the source agent. Hence, they apply in much stronger models of communication, such as ones that allow an agent to send messages to multiple destinations at the same round, and ones that consider non-anonymous populations, where an agent could direct a message to a desired destination. Note that the same arguments hold also for the noisy majority-consensus problem if the initial subset A of agents is small. On the other hand, without interacting with other agents and simply waiting to receive sufficiently many samples from the source agent, the noisy rumor-spreading problem could only be solved in $O(\frac{1}{\epsilon^2} n \log n)$ rounds.

1.5 Our results

We present a randomized symmetric algorithm that solves the noisy rumor-spreading problem in $O(\frac{1}{\epsilon} \log n)$ rounds and uses a total of $O(\frac{1}{\epsilon^2} n \log n)$ messages (or bits). These bounds are both asymptotically optimal and, in fact, are as fast and message efficient as if each agent would have been simultaneously informed by the environment directly. We also show that the same asymptotically tight bounds (for the running time and message complexity) hold also for solving the noisy majority-consensus problem with any initial subset A of agents of size $|A| = \Omega(\frac{1}{\epsilon^2} \log n)$ and whose majority-bias is $\Omega(\sqrt{\log n/|A|})$.

Throughout most of this paper, we assume that all nodes start the execution simultaneously at the same time. In Section 3 we show how to remove this assumption. This modification applies to both algorithms and comes at an additive cost of $O(\log^2 n)$ to the running time, while the message complexity remains the same.

Our results imply that even in severely restricted, stochastic and noisy settings one can still solve the noisy rumor-spreading and the noisy majority-consensus problems efficiently by applying simple protocols. Indeed, our basic algorithms employ very simple rules that can be implemented using restricted memory, specifically, using $O(\log \log n + \log(1/\epsilon))$ memory bits. Essentially, each agent has some waiting period (in which it does not send any message), and after which it starts sending its current opinion at each round until the protocol terminates. Furthermore, its opinion is occasionally updated following a majority-type procedure based on its recently received messages.

¹One could view this trait as a consequence of a symmetry of the world, in which an agent can decide if two opinions are the same or not but has no access to their actual values. For example, a flock of birds following a source (e.g., a bird that has spotted a predator) that travels either north or south can do this even in an environment where there is complete symmetry between these two directions. The only demand is that the escape direction of all birds agree with that of the source.

Our algorithms seem to rely on synchronization, at least to some extent. Although it is not realistic to assume that biological ensembles are highly synchronous, some degree of synchronicity may still exist [12, 34]. (For example, agents could potentially differentiate large enough windows of time considering each such window as a round.) Moreover, our algorithms do not actually employ synchronization in a strong sense, instead, they use synchronization mostly to ensure that propagation of local broadcasts are somewhat balanced. If this is guaranteed, it seems reasonable that algorithms in the spirit of what we propose may still work, even if the system is not highly synchronized. In this preliminary work, we assume synchronization to ease the mathematical analysis and presentation of our algorithms.

1.6 Insights on the Difficulty of the Problem

We first note that when the bias is small, solving the majority-consensus problem using small size messages is difficult even without accounting for noise, i.e., even assuming the communication is always reliable. Indeed, under reliable communication², this task was studied by Angluin et al. in the particular case of A being the set of all n agents [6]. The authors in [6] showed that in their model, the problem can be solved in $O(\log n)$ rounds.

We note that for our purposes, we could not use variants of the algorithm in [6] not only because it is not robust under communication noise, but also because it inherently uses *three* symbols in the communication, while we are restricted to only *two* symbols (a single opinion). Indeed, our construction is based on different principles.

Before we describe our algorithms, let us first highlight some of the complex features of the noisy rumor-spreading problem (the same difficulties arise also in the noisy majority-consensus problem). Consider an agent a that receives its first message. This agent now has several options for its actions. One option is to keep silent (wait) until receiving another message. This strategy would result in an algorithm that requires huge amount of time. Indeed, the first agent that hears two messages must hear both of them from the source (since all other agents are silent), and this would require waiting for $\Omega(\sqrt{n})$ rounds, by the birthday paradox. Another possible action for such an agent is to immediately forward the message it just received to others. This strategy would result in the typical agent hearing a very unreliable message for the first time. That is, the number of intermediate agents on the path between the source and the typical agent would be of size roughly $\log n$. Now, each time the message passes from an agent to an agent, the probability of preserving the original opinion drastically reduces. Specifically, it is not difficult to show that a message following a path of size c is correct with probability at most $1/2 + (2\epsilon)^c$. This means that if ϵ is small, the probability that a typical agent receives the correct opinion on the first message it hears is at most $1/2 + 1/n$. If this is the case with all agents, it seems, again, almost impossible to recover and reconstruct the correct opinion \mathcal{B} . Another difficulty in the strategy of immediately forwarding messages, is that the execution seems to be dependent on the quality of messages received directly from the source by the first few agents, and these messages can be corrupted with non-negligible probability. Indeed, in the beginning of the execution, the pattern of meeting looks like a tree, rooted at the source agent. Moreover, the collection of subtrees hanging down from the children of the root (the agents directly informed by the source agent) do not have the same size, as the subtrees hanging down from the first informed children of the root grow much faster and dominate the population. Hence, the initial opinion of agents could not be more reliable than the initial opinions of the roots of the corresponding subtrees. At this point, with non-negligible probability, the majority of agents would have obtained the wrong opinion, from which it seems again almost impossible to recover.

To overcome these difficulties, we use a third option for the behavior of an agent, allowing it to wait for a prescribed number of rounds before sending a message. For doing so, we rely on synchronization, which we use to balance the sizes of the aforementioned subtrees and, therefore, constrain the deterioration of reliability.

²The algorithm in [6] is robust under a very small fraction of agents being Byzantine, but is not robust under communication noise.

2 Algorithms

The interesting cases are when ϵ is a small constant, but we allow it to be much smaller. Specifically, let $\epsilon > 1/n^{1/2-\eta}$, for some arbitrarily small constant $\eta > 0$. We present symmetric and simple randomized algorithms that solve the noisy rumor-spreading and the majority-consensus problems. The running times and message complexities of both algorithms are asymptotically optimal, that is, they both terminate after $O(\frac{1}{\epsilon^2} \log n)$ rounds and use a total of $O(\frac{1}{\epsilon^2} n \log n)$ messages.

Although our algorithms are simple, their analysis is quite involved. Most of the technical ideas in this paper are used for the analysis of our noisy rumor-spreading algorithm, hence we focus on this algorithm. The algorithm consists of two stages. The first stage of the algorithm is intended to *activate* all agents (an agent is considered as activated upon receiving its first message), and to make sure that overall, the average initial opinion of activated agents has some non-negligible bias towards the correct opinion. Stage 2 of the algorithm is meant to boost the bias using repeated samplings until consensus is reached.

2.1 Stage 1: Spreading the Information

2.1.1 Intuition

For spreading the correct opinion \mathcal{B} while controlling the deterioration of the average bias of informed agents towards \mathcal{B} , the first idea we employ is to delay propagation of messages, and synchronize them, by grouping the time slots into *phases*. That is, we propagate the information in layers, forming a tree, whose root is the source agent S (layer 0). To control the reliability deterioration of the messages, we synchronize the phases so that all activated agents broadcast in a phase at the same time (actually, we could allow some flexibility in these assumptions, and only require broadcasting in a phase at roughly the same time). In particular, in the first phase, called phase 0, only the source agent transmits messages (all non-source agents are waiting). Recall that every such message is correct with probability at least $1/2 + \epsilon$. Phase 0 lasts for $\beta_s := \Theta(\frac{1}{\epsilon^2} \log n)$ rounds, and is meant to allow the source agent to directly inform sufficiently many agents, and guarantee that with high probability the bias of these agents towards \mathcal{B} is bounded away from zero, specifically, the bias is at least $\epsilon/2$. Note that at this point, we are left with solving the noisy majority-consensus problem with an initial set A of agents of size $\Theta(\frac{1}{\epsilon^2} \log n)$ whose majority-bias is $\Omega(\sqrt{\log n/|A|})$.

The general description of our algorithm in stage 1 is as follows: any agent receiving a message in some phase i (also including the case $i = 0$) sets the value of this message as its *initial opinion*, keeps *silent* (waits, and does not send messages) until phase i is completed and only then does it start sending messages. When the next phase $i + 1$ starts, each such agent will start to send its initial opinion repeatedly in every round until the whole of stage 1 is completed. Hence, phase i is responsible for passing information between all the already activated agents (these are the agents in layers $0, 1, \dots, i - 1$) to the newly activated agents in phase i (forming layer i).

Because of the noise in the messages, the quality of information that propagates between layers deteriorates exponentially fast in ϵ . Specifically, if the fraction of correct agents at layer i is some $1/2 + \delta_i$, then the expected fraction of correct messages reaching agents at layer $i + 1$ is $1/2 + 2\epsilon\delta_i$. To guarantee that this controlled level of deterioration holds w.h.p., as well as to account for this already problematic phenomena, our phasing process makes sure that the number of agents informed in the next layer increases quadratically faster than the deterioration factor. Specifically, the number of newly informed agents increases by a factor larger than $1/\epsilon^2$. Maintaining this property throughout all phases allows us to guarantee that when x agents are activated (where x is sufficiently large), then, w.h.p., the bias towards the correct opinion is $\Omega(\sqrt{\log n/x})$. In particular, this implies that when all n agents are activated, the bias towards the correct opinion is $\Omega(\sqrt{\log n/n})$.

2.1.2 Formal Description of Stage 1

Choose parameters $f, \beta, s = \Theta(1/\epsilon^2)$ such that $f > c_1\beta > c_2s > c_3/\epsilon^2$, for sufficiently large constants $c_1, c_2, c_3 > 0$. Let $\beta_s = s \log n$, and $\beta_f = f \log n$. In addition, let $T = \lfloor \log(n/2\beta_s)/\log(\beta + 1) \rfloor$. Note that $\beta_s(\beta + 1)^T \leq n/2$ and that $T = O(\frac{\log n}{\log(1/\epsilon)})$. We group the rounds of stage 1 into $T + 2$ phases, such that for each $0 \leq i \leq T$, phase $i + 1$ immediately follows phase i . Phase 0 takes β_s rounds, phase i , for $1 \leq i \leq T$, takes β rounds, and phase $T + 1$ takes β_f rounds. Formally, letting $[x, y)$ denote the time period from round x

until round $y - 1$, we have: phase 0 = $[0, \beta_s)$, for $1 \leq i \leq T$, phase $i = [\beta_s + (i - 1)\beta, \beta_s + i\beta)$, and, phase $T + 1 = [\beta_s + T\beta, \beta_s + T\beta + \beta_f)$.

At a given time, a non-source agent is called *activated* if it already heard a message by that time (the source agent is always considered activated). A non-activated agent is called *dormant*. For an agent a , let t_a denote the first time a was activated, and let its *initial opinion* $\mathcal{B}_0(a)$ be the opinion it heard at that time. An activated agent is called *initially correct* if the message it heard for the first time is correct, i.e., if $\mathcal{B}_0(a) = \mathcal{B}$. Let i_a be the integer i for which t_a belongs to phase i .

The rule of stage 1: An activated agent a acts as follows. If $i_a \leq T$ the agent sends its initial opinion $\mathcal{B}_0(a)$ in each round during the phases $i_a + 1, i_a + 2, \dots, T + 1$. (In other words, Agent a waits until phase i_a is completed and then it starts sending its initial opinion repeatedly in every round until the end of stage 1.)

Note first, that in particular, in phase 0, the source S is the only agent sending any messages. Let X_0 be the number of agents activated at phase 0.

Claim 2.1. *By choosing $s > c/\epsilon^2$ for a large enough constant c , it is guaranteed that at the end of phase 0, w.h.p., we have $\beta_s/3 \leq X_0 \leq \beta_s$ activated agents whose bias towards the correct opinion \mathcal{B} is at least $\epsilon/2$.*

Proof. Let Z_0 denote the number of initially correct agents among the Y_0 agents that were activated during phase 0 and let ϵ_0 be such that $Z_0 = (1/2 + \epsilon_0)Y_0$. Our goal is to show that $\epsilon_0 \geq \epsilon/2$.

Recall that phase 0 lasts for $\beta_s = s \log n$ rounds, and that until the phase is completed only the source agent S is sending messages. Hence, during phase 0, there are always at most β_s activated agents, and in particular, at least $n/2$ dormant agents. Hence, each message sent during phase 0 has probability at least $1/2$ to activate an agent. The expected number of activated agents at the end of phase 0 is thus at least $\beta_s/2$. By a simple generalization of Chernoff's inequality, we can choose the constant s (in the definition of β_s) to be a sufficiently large constant so that w.h.p., at the end of phase 0, we have at least $\beta_s/3$ activated agents, that is, $X_0 = Y_0 \geq \beta_s/3$.

Let us now focus on the random faults occurring in the messages sent during phase 0. Each of the Y_0 activated agents has probability at least $1/2 + \epsilon_s \geq 1/2 + \epsilon$ to be activated with the correct opinion \mathcal{B} . Hence, by linearity of expectation, the expected number of agents that were activated up with the correct opinion during phase 0 is at least $(1/2 + \epsilon)Y_0$. Since $Y_0 \geq \beta_s/3 = (s/3) \log n$, it follows from Chernoff's inequality that by taking $s \gg 1/\epsilon^2$, we can ensure that w.h.p., the number of initially correct agents during phase 0 is $Z_0 > (1/2 + \epsilon/2)Y_0$, that is, w.h.p., we have $\epsilon_0 \geq \epsilon/2$. This establishes the proof of the claim. \square

Observe that by Claim 2.1, phase 0 essentially reduces the noisy rumor-spreading problem to an instance of the noisy majority-consensus problem, with an initial set of size $X_0 = \Theta(\beta_s) = \Theta(\frac{1}{\epsilon^2} \log n)$ and majority-bias of at least $\epsilon/2 = \Omega(\sqrt{\log n / |X_0|})$. What we shall show in the remainder of this subsection is that in general, phases 0, 1, \dots, i , where $i \leq T + 1$, take us to an instance of the noisy majority-consensus problem, with an initial set A_i of size $|A_i| = \Theta(\frac{1}{\epsilon^{2i+2}} \log n)$ and majority-bias of at least $\epsilon^{i+1}/2 = \Omega(\sqrt{\log n / |A_i|})$. For $T = \lceil \log(n/2\beta_s) / \log(\beta + 1) \rceil$ this would lead to the following lemma summarizing the performances of stage 1.

Lemma 2.2. *Stage 1 takes $O(\frac{1}{\epsilon^2} \log n)$ rounds. At the end of the stage the following event E holds w.h.p.:*

1. *All agents are activated.*
2. *The fraction of initially correct agents is at least $1/2 + \Omega(\sqrt{\log n / n})$.*

The remainder of this subsection is devoted to the proof of Lemma 2.2. It is easy to verify that the number of rounds in stage 1 is $\beta_s + \beta T + \beta_f = O(\frac{1}{\epsilon^2} \log n)$. Our goal thus is to show that event E mentioned in the lemma holds with high probability. The proof considers a sequence of events E_1, E_2, \dots, E_τ , for some $\tau = O(\log n)$, where $E_\tau = E$. We will show that event E_i occurs w.h.p., given E_{i-1} . This would imply that E occurs w.h.p., by repeatedly invoking the standard argument $|\Pr(E_{i+1} | E_i) - \Pr(E_{i+1})| \leq \Pr(\bar{E}_i)$.

Let i be a non-negative integer. Define X_i as the random variable indicating the number of agents that were activated at some time before the end of phase i . Let Y_i denote the random variable indicating the

number of agents that were activated during phase i . Hence, we have: $X_i = \sum_{j=0}^i Y_j$. Let Z_i denote the number of initially correct agents among the Y_i agents that were activated during phase i and let ϵ_i be such that $Z_i = (1/2 + \epsilon_i)Y_i$. Recall that Claim 2.1 asserts that w.h.p., we have $\beta_s/3 \leq X_0 \leq \beta_s$ and $\epsilon_0 \geq \epsilon/2$. In what follows, we assume that this highly likely event holds (see the paragraph above).

Analysis for phase i , where $1 \leq i \leq T$: It is easy to see that X_i , the number of activated agents at the end of phase i is at most $X_i \leq (\beta + 1)^i X_0 = O\left(\frac{1}{\epsilon^{2i+2}} \log n\right)$. This follows trivially from the fact that $X_i = X_{i-1} + Y_i$, and from the fact that $Y_i \leq \beta X_{i-1}$ (because for $i \geq 1$, phase i is composed of β rounds and in each such round precisely X_{i-1} messages are being sent). The following claim states that w.h.p., the value of X_i is, in fact, very close to $(\beta + 1)^i X_0$. Establishing this claim will enable us to show that up to phase T , the values Y_i are increasing exponentially and that at the beginning of phase T we already have $\Omega(\epsilon^2 n)$ activated agents. The proof of the claim extensively uses concentration properties given by Chernoff's inequality and is deferred to the full version:

Claim 2.3. *W.h.p., for every i , $1 \leq i \leq T$, we have: $(\beta + 1)^i X_0/8 \leq X_i \leq (\beta + 1)^i X_0$.*

Relying on the definition of T , the fact that $X_0 \geq \beta_s/3$ holds w.h.p., and taking $\beta = O(1/\epsilon^2)$ such that $\beta > 3s$, we ensure that $(\beta + 1)^{T+1} X_0 \geq n/6$. Hence, Claim 2.3 implies the following lower bound on X_T , the number of activated agents at the beginning of the last phase in stage 1.

Corollary 2.4. *W.h.p., we have $X_T = \Omega((\beta + 1)^T X_0) = \Omega(\epsilon^2 n)$.*

Recall that phase $T+1$ consists of $\beta_f = f \log n$ rounds, in which all X_T agents that were activated before the beginning of the phase are sending their initial opinion in each round of the phase. Hence, Corollary 2.4 implies that by setting f such that $f > c/\epsilon^2$ for large enough constant c , we obtain the first part of Lemma 2.2. That is, we have:

Corollary 2.5. *W.h.p., at the end of stage 1, all agents are activated.*

The next corollary gives a lower bound on the growth of Y_i , the number of newly activated agents in phase $i = 1 \dots T+1$. This lower bound will be used for bounding the bias from below (see Claim 2.7). Note that the duration of the last phase, $T+1$, is taken to be longer than that of phases $i = 1 \dots T$ to guarantee a large number of newly activated agents even in this last phase. Indeed, continuing with phases of duration β would activate all agents relatively early, but would also restrict the number of newly activated agents at later phases.

Corollary 2.6. *W.h.p., for every phase i , where $1 \leq i \leq T+1$, we have $Y_i \geq \beta^{i-1} \log n$.*

Recall that $1/2 + \epsilon_i$ is the fraction of initially correct agents among the Y_i agents that were activated in phase i , i.e., ϵ_i is the bias toward \mathcal{B} among these Y_i agents. Corollary 2.6 will be useful for obtaining the following claim.

Claim 2.7. *W.h.p., for every phase i , where $0 \leq i \leq T+1$, we have $\epsilon_i \geq \epsilon^{i+1}/2$.*

We prove the claim by induction on i . The basis of the induction is $i = 0$, which has already been established in Claim 2.1. Consider now phase i , where $1 \leq i \leq T+1$. Fix the configuration at the end of phase $i-1$ and let $\phi = \epsilon_{i-1}$. By the induction hypothesis, we can assume that $\phi \geq \epsilon^i/2$. Moreover, we can assume that the fraction of initially correct agents among the X_{i-1} activated agents in the beginning of phase i is at least $1/2 + \phi \geq 1/2 + \epsilon^i/2$. For any of the newly activated agents a in phase i , the probability that the initial opinion of a is correct is at least $(1/2 + \phi) \cdot (1/2 + \epsilon) + (1/2 - \phi) \cdot (1/2 - \epsilon) = 1/2 + 2\epsilon\phi$. By linearity of expectation, this equation implies that $E(Z_i) \geq (1/2 + 2\epsilon\phi)Y_i \geq (1/2 + \epsilon^{i+1})Y_i$. Taking $\delta = \epsilon^{i+1}/2$ gives $(1 - \delta)E(Z_i) > Y_i(1/2 + \epsilon^{i+1}/2)$. We now apply Chernoff's inequality and rely on the fact that Y_i is large, as promised by Corollary 2.6. $\Pr[Z_i < Y_i(1/2 + \epsilon^{i+1}/2)] \leq e^{-\delta^2 E(Z_i)/2} < e^{-\delta^2 Y_i/4} = e^{-\epsilon^{2i+2} Y_i/16} = 1/e^{\Omega(\epsilon^{2i} \beta^{i-1} \log n)}$. Taking $\beta > 3/\epsilon^2$ to be sufficiently large therefore implies that w.h.p., we have $Z_i \geq Y_i(1/2 + \epsilon^{i+1}/2)$, or in other words, $\epsilon_i \geq \epsilon^{i+1}/2$. This establishes the proof of Claim 2.7, which implies that w.h.p., the fraction of initially correct agents at the end of stage 1 is at least $1/2 + \epsilon^{T+2}/2 = 1/2 + \Omega(\sqrt{\log n}/n)$ (the equation follows by the definition of T , and the fact that $\beta > 1/\epsilon^2$). This completes the proof of Lemma 2.2.

2.2 Stage 2: Boosting the Bias

2.2.1 Intuition

We proved that, w.h.p., at the end of Stage 1 all agents are activated and the fraction of correct agents is at least δ_1 , where $\delta_1 = \Omega(\sqrt{\log n/n})$. Stage 2 is meant to gradually boost the bias towards the correct opinion, so that, w.h.p., it will equal 1 (that is, all agents are correct) at the end of the stage. We note that since the initial bias of δ_1 is very close to 0, the task of boosting the majority opinion of a population is difficult even without accounting for noise, i.e., even assuming the communication is always reliable (see the discussion in Subsection 1.6 regarding the work in [6]).

Stage 2 is executed in $k + 1$ phases, where $k = \lceil \log(1/\delta_1) \rceil = O(\log n)$. Informally, phase i , for $1 \leq i \leq k$, is associated with a parameter δ_i , such that it is guaranteed w.h.p., that when the phase starts, the fraction of correct agents is at least $1/2 + \delta_i$. (Note that a sample from such a population is correct with strictly smaller probability than $1/2 + \delta_i$, because of noise.) Essentially, in phase i , each agent takes $\gamma = O(1/\epsilon^2)$ samples from the population (during γ rounds) and then sets its opinion according to the majority opinion of these samples. Despite the noise in the samples, we will prove that, as long as δ_i is sufficiently small, this majority process increases the fraction of correct agents, w.h.p., from $1/2 + \delta_i$ to at least $1/2 + 2\delta_i$. Moreover, we shall prove that if δ_i is large, then the majority process does not decrease δ_i too much. Hence, for the next phase, we can safely assume that either $\delta_{i+1} = 2\delta_i$ or that δ_{i+1} is already sufficiently large.

To establish the required boosting, the fact that δ_i may be very small prevented us from directly applying Chernoff's inequality and instead required us to come up with more involved arguments. To lower bound the probability that the majority opinion in the γ samples is correct, we perceive the samples as obtained by an imaginary process composed of two steps taken over γ players. In the first step, for each player we flip a *fair* coin which determines its opinion (i.e., probability $1/2$ for having each opinion). Then, at the second step, each of the players with the wrong opinion, (independently) has a small probability (close to δ_i) of flipping its opinion to the correct one. The parameters are chosen such that at the end of this imaginary process, the probability that the majority opinion among the γ players is correct is the same as probability that the majority opinion in the original γ samples is correct. To bound the latter probability, we thus analyze the imaginary two-step process. Informally, the imaginary process allows us to understand the situation in a more modular manner. Indeed, the probability that the first step is successful (yielding a correct majority) is precisely $1/2$, and once the first-step is successful, the second step cannot harm the situation. If the first step turns out to be unsuccessful, then before the second step starts there are $\gamma/2 + x$ wrong players and $\gamma/2 - x$ correct ones, for some integer x . When x is small, Stirling's formula comes handy for bounding from below the probability that such a situation occurs after the first step. Specifically, this probability is $\Omega(x/\sqrt{\gamma})$. For such a situation to be fixed, we need that in the second step, at least $x + 1$ wrong players flip their opinion. By carefully analyzing the probability of such a corrective event, we make sure that all together the majority is correct with probability $\min\{1/2 + 2^5\delta_i, 5/9\}$.

A direct application of Chernoff's inequality, relying on the fact that $\delta_i = \Omega(\sqrt{\log n/n})$, will then show that w.h.p., the bias increases from δ_i at phase i to at least $\min\{2^3\delta_i, 1/40\}$ at phase $i + 1$. Hence, after invoking $k = \lceil \log(1/\delta_1) \rceil = O(\log n)$ phases, the fraction of correct agents becomes bounded away from $1/2$ by an additive constant. Hence, to achieve high probability that all agents are correct, it is sufficient that in the last phase, namely phase $k + 1$, each agent takes $O(\frac{1}{\epsilon^2} \log n)$ samples of the population, and sets its opinion according to the majority opinion in these samples.

2.2.2 Formal description of Stage 2

As guaranteed by Lemma 2.2, at the end of stage 1, w.h.p., all agents are activated and the bias of their initial opinion towards \mathcal{B} is $\Omega(\sqrt{\log n/n})$. Hence, stage 1 brings us to an instance of the majority-consensus problem, where the set A contains the whole population and the majority-bias is $\Omega(\sqrt{\log n/|A|})$. Stage 2 is meant to solve this problem.

Let $r = \lceil 2^{20}/\epsilon^2 \rceil$, and let $\gamma = 2r + 1$ (no attempt has been made to minimize the constant factors). We define $k = O(\log n)$ and take stage 2 to be composed of $k + 1$ phases. Each of the first k phases has $2\gamma = O(1/\epsilon^2)$ rounds, while phase $k + 1$ is composed of $O(\frac{1}{\epsilon^2} \log n)$ rounds. Essentially, in each phase of the stage, agents repeatedly send their current opinion. At the end of the phase, agents may choose to update their opinion (essentially set to be the majority opinion among the opinions received in the phase). Since

the opinion of an agent may be updated only at the end of a phase, all messages sent by an agent during any given phase are the same. For a phase i , let m_i denote the number of rounds in the phase (i.e., $m_i = 2\gamma$ for $i = 1, \dots, k$, and $m_{k+1} = O(\frac{1}{\epsilon^2} \log n)$). During phase i , an agent that received at least $m_i/2$ messages is called *successful* and the messages it received are called *samples*. Since all agents are sending messages in each round then, w.h.p., at least half of the population will be successful in each phase. Only the successful agents in the phase will update their opinion at the end of the phase, while the rest will remain with their previous opinion.

The rule of stage 2: For each round in each phase i , where $1 \leq i \leq k+1$, each agent repeatedly sends its current opinion (each time to an arbitrary other agent). The opinion of an agent in phase 1 of stage 2 is its initial opinion. At the end of each phase, a successful agent in the phase will consider only the first $m_i/2$ samples it received and update its opinion according to the majority opinion in these samples.

Lemma 2.8. *Consider taking $\gamma = 2r + 1$ (noisy) samples from a population whose bias towards the correct opinion is at least δ . Then, the probability that the majority of these γ samples is correct is at least $\min\{1/2 + 4\delta, 1/2 + 1/100\}$.*

Proof. Consider the $\gamma = 2r + 1$ samples. We say that a sample is *correct* if it holds the correct opinion \mathcal{B} . The γ samples are chosen independently, and uniformly at random, among the population whose bias towards the correct opinion is at least δ . Let $b = 2\epsilon\delta$. Accounting for the noise in the samples, for each sample, the probability that the sample is correct is at least: $(1/2 + \delta) \cdot (1/2 + \epsilon) + (1/2 - \delta) \cdot (1/2 - \epsilon) = 1/2 + 2\epsilon\delta = 1/2 + b$. Note that b may be very small, so directly employing Chernoff's inequality over the γ samples would not imply the desired bound. Instead, let us look at the following imaginary two-step process that forms an equivalent view of the γ samplings.

The imaginary process is performed over a set S consisting of γ (boolean) players, namely, $S = \sigma_1, \sigma_2, \dots, \sigma_\gamma$.

- **First step:** each player σ_j flips a fair coin to form an initial opinion (i.e., a bit in $\{0, 1\}$).
- **Second step:** independently with probability $2b$, each player σ_j gets to see the correct opinion \mathcal{B} and corrects its opinion if it was wrong initially (otherwise it remains with its correct opinion).

Note that after this two-step process, the probability that a player is correct is precisely $1 - \frac{1}{2}(1 - 2b) = 1/2 + b$. Thus, the probability that the majority opinion among the γ players is \mathcal{B} bounds from below the probability that the majority of the original γ samples gathered by agent a is \mathcal{B} . To lower bound this latter probability, in what follows, we focus on the γ players, in the two-step process. Let x be a positive integer. Define the following events.

- C = at the end of the first step, the majority of players in S is correct.
- U_x = after the first step, the number w of wrong players in S satisfies $r + 1 \leq w \leq r + x$.
- F_x = in the second step, the number of opinion flips is at least x .
- F = the majority opinion at the end of the two-steps is correct.

Our goal is to lower bound the probability that F occurs. Note first that $\Pr(C) = 1/2$. Assume now that C did not occur, hence U_x occurred for some x , that is, in S , the first step results in a set W of wrong players whose size w satisfies $r + 1 \leq w \leq r + x$. In this case, for F to occur, it is sufficient that event F_x would occur in the second step. That is, for every positive integer x , we have:

$$\Pr(F) \geq \Pr(C) + \Pr(F_x \mid U_x) \cdot \Pr(U_x). \quad (1)$$

Stirling's formula can be used to lower bound the probability that U_x occurs, when x is a small integer. The bound is indicated by the following claim:

Claim 2.9. *For $1 \leq x \leq \sqrt{r}$, we have $\Pr(U_x) > x/10\sqrt{r}$.*

Proof. For each j , let $P(j)$ denote the probability that precisely j players in S hold the wrong opinion after the first step. We rely on the fact that the coins tossed in the first step are fair, and on Stirling's formula to show that for $0 \leq i \leq \sqrt{r}$, we have $P(r+i) > 1/2\sqrt{r}$. This will establish the claim since for $x \leq \sqrt{r}$, the probability that Event U_x occurs is $\Pr(U_x) = \sum_{i=0}^x P(r+i) > x/2\sqrt{r}$.

For completeness, the bound on $P(r+1)$ can be obtained as follows:

$$\begin{aligned} P(r+i) &= 2^{-2r} \binom{2r}{r+i} = 2^{-2r} \frac{2r!}{(r-i)!(r+i)!} \geq \\ &\geq 2^{-2r} \frac{2r!}{(r-\sqrt{r})!(r+\sqrt{r})!}. \end{aligned}$$

Applying Stirling's formula on the right side of the equation, we get as desired:

$$\begin{aligned} P(r+i) &> \frac{r^{2r}}{(r-\sqrt{r})^{r-\sqrt{r}}(r+\sqrt{r})^{r+\sqrt{r}}} \cdot \frac{1}{\sqrt{3\pi r}} \\ &= \frac{1}{\sqrt{3\pi r}} \cdot \frac{r^{r-\sqrt{r}}}{(r-\sqrt{r})^{r-\sqrt{r}}} \cdot \frac{r^{r+\sqrt{r}}}{(r+\sqrt{r})^{r+\sqrt{r}}} \\ &= \frac{1}{\sqrt{3\pi r}} \cdot \frac{1}{(1-\frac{\sqrt{r}}{r})^{r-\sqrt{r}}} \cdot \frac{1}{(1+\frac{\sqrt{r}}{r})^{r+\sqrt{r}}} \\ &= \frac{1}{\sqrt{3\pi r}} \cdot \frac{1}{(1-\frac{1}{r})^{r-\sqrt{r}}} \cdot \frac{1}{(1+\frac{1}{\sqrt{r}})^{2\sqrt{r}}} \\ &> \frac{1}{\sqrt{3\pi r}} \cdot \frac{1}{e^{-0.9}} \cdot \frac{1}{e^2} > \frac{1}{10\sqrt{r}}. \end{aligned}$$

□

To successfully use Equation 1, we need to bound from below the value of $\Pr(F_x | U_x)$, that is, the probability that given U_x , at least x players (in W) flip their opinion in the second step.

Claim 2.10. (1) If $r-1 \leq 2/b$ then $\Pr(F_1 | U_1) \geq 2rb/e^4$. (2) If $rb > 2$, then for $x \leq \lceil rb \rceil$, $\Pr(F_x | U_x) \geq 1/3$.

Proof. Recall that in the second step, each of the wrong players flips its opinion with probability $2b$. Observe that $\Pr(F_1 | U_1)$ is bounded from below by the probability that precisely one of the first r wrong players in W flipped its opinion in the second step (note, $|W| = r+1$ since U_1 occurred). This latter probability is $r \cdot 2b(1-2b)^{r-1}$, which is at least $2rb/e^4$, if $r-1 \leq 2/b$. This establishes the first part of the claim. Let us now turn to prove the second part of the claim. Assume that $rb > 2$. Note that the expected number of flips in W is at least $2rb > 4$. Chernoff's inequality therefore implies that the probability that the number of flips in W is at most rb is bounded from above by $1/e^{1/2}$, implying that for integer $x \leq \lceil rb \rceil$, we have: $\Pr(F_x | U_x) \geq \Pr(F_{\lceil rb \rceil} | U_x) \geq 1 - 1/e^{1/2} > 1/3$. □

Finally, to establish Lemma 2.8, we combine Equation 1 with Claims 2.9 and 2.10 for different values of δ .

The case of small δ : Consider the case that $\delta \leq \epsilon/2^{20}$. This restriction on δ implies that $rb \leq 2$. In this case, Claim 2.10 tells us that $\Pr(F_1 | U_1) \geq 2rb/e^4$. Hence, by Claim 2.9 and Equation 1, we have: $\Pr(F) \geq \Pr(C) + \Pr(U_1)\Pr(F_1 | U_1) > 1/2 + (1/10\sqrt{r})(2rb/e^4) > 1/2 + 4\delta$.

The case of medium δ : Consider the case that $\epsilon/2^{20} < \delta < 1/2^{12}$. In this case, we have $4 < 2rb \leq 2(\sqrt{r}-1)$. Let us set $x := \lceil rb \rceil$. Hence, $1 \leq x \leq \sqrt{r}$, and we can employ Claim 2.9, yielding $\Pr(U_x) > x/10\sqrt{r}$. By the second part of Claim 2.10, we obtain: $\Pr(F) \geq \Pr(C) + \Pr(U_x) \cdot \Pr(F_x | U_x) \geq 1/2 + (x/10\sqrt{r})/3 \geq 1/2 + b\sqrt{r}/30 > 1/2 + 4\delta$.

The case of large δ : Consider the case that $\delta \geq 1/2^{12}$. In this case, we set $x := \lceil \sqrt{r}/3 \rceil$. Since $\lceil \sqrt{r}/3 \rceil < \lceil rb \rceil$, the second part of Claim 2.10 implies that $\Pr(F_x | U_x) \geq 1/3$. Hence, we get: $\Pr(F) \geq \Pr(C) + \Pr(U_x) \cdot \Pr(F_x | U_x) \geq 1/2 + x/30\sqrt{r} \geq 1/2 + 1/100$. This completes the proof of Lemma 2.8. □

Corollary 2.11. *After the first $k = \log(\sqrt{n/\log n})$ phases, w.h.p., the fraction of correct agents is at least $1/2 + 1/400$.*

Proof. Consider a phase i , for $1 \leq i \leq k$. Assume that phase i starts when the fraction of agents having the correct opinion is at least $1/2 + \delta_i$. The number of successful agents in the phase are w.h.p, at least $n/2$. Hence, by applying Chernoff bound, using Lemma 2.8 and relying on the fact that $\delta_i > \sqrt{\log n/n}$, we get that w.h.p., among the successful agents in the phase, the fraction of agents that correctly update their opinion at the end of the phase is at least

$$\min\{1/2 + 3\delta_i, 1/2 + 1/200\}.$$

Altogether, the number of correct agents at the end of the phase is at least: $\frac{n}{2}(1/2 + \delta_i) + \frac{n}{2}(1/2 + \min\{3\delta_i, 1/200\}) = n \cdot (1/2 + \min\{2\delta_i, 1/400\})$.

Hence, since $\delta_1 \geq \sqrt{\log n/n}$, then after applying $k = \log(\sqrt{n/\log n})$ phases, w.h.p., the fraction of correct agents becomes at least $1/2 + 1/400$, as desired. \square

In the final phase, namely phase $k + 1$, each agent collects $O(\frac{1}{\epsilon^2} \log n)$ independent samples, uniformly at random, from a population whose bias towards the correct opinion is at least $1/400$. Assuming the constant hiding behind the O -otation is sufficiently large, Chernoff's inequality guarantees that, w.h.p., the majority opinion of such samples is correct. Hence, a union bound argument guarantees that w.h.p, all agents are correct at the end of stage 2. Let us now analyze the running time of stage 2. Each of the first k phases takes $\gamma = O(1/\epsilon^2)$ rounds. Since $k = O(\log n)$, the number of rounds required to perform the first k phases is $O(\frac{1}{\epsilon^2} \log n)$. The running time of phase $k + 1$ is $O(\frac{1}{\epsilon^2} \log n)$. Altogether, we obtain the following.

Lemma 2.12. *Stage 2 takes $O(\frac{1}{\epsilon^2} \log n)$ rounds and at the end of the stage all agents are correct, with high probability.*

Lemmas 2.2 and 2.12 yield that our algorithm solves the noisy rumor-spreading problem in $O(\frac{1}{\epsilon^2} \log n)$ rounds. Since each message is composed of a single bit, and since in each round, each agent can send at most one message, we get the bound $O(\frac{1}{\epsilon^2} n \log n)$ on the total number of messages and bits sent. Altogether, we obtain the following.

Theorem 2.13. *The noisy rumor-spreading problem can be solved using $O(\frac{1}{\epsilon^2} \log n)$ rounds, and a total of $O(\frac{1}{\epsilon^2} n \log n)$ messages (or bits).*

Corollary 2.14. *Consider the noisy majority-consensus problem with an initial set A of at least $\Omega(\frac{1}{\epsilon^2} \log n)$ agents and majority-bias of $\Omega(\sqrt{\log n/|A|})$. This problem can be solved in $O(\frac{1}{\epsilon^2} \log n)$ rounds, and using a total of $O(\frac{1}{\epsilon^2} n \log n)$ messages (or bits).*

Proof. Recall that Claim 2.1 implies that after phase 0 is completed, we are left with solving the noisy majority-consensus problem with an initial set A_0 of agents of size $|A_0| = \Theta(\frac{1}{\epsilon^2} \log n)$ whose majority-bias is $\Omega(\sqrt{\log n/|A_0|})$. As we saw, this problem is solved by applying the remaining phases $i = 1, \dots, T + 1$ of stage 1, and then applying stage 2. Specifically, as given by Claims 2.7 and 2.3, phase i of stage 1, for each $i \in \{1, \dots, T + 1\}$, reduced the problem to the noisy majority-consensus problem with an initial set A_i of size $A_i = \Theta(\frac{1}{\epsilon^{2i+2}} \log n)$ and majority-bias of $\Omega(\sqrt{\log n/|A_i|})$. Hence, after applying stage 1, we were left with dealing with the noisy majority-consensus problem with an initial set X of agents composed of all n agents and majority-bias of $\Omega(\sqrt{\log n/n})$. Solving this latter problem is precisely the objective of stage 2.

In light of this, the general case of the noisy majority-consensus problem can be solved as follows. Recall, in this problem we consider an initial subset A of agents of size $|A| = \Omega(\frac{1}{\epsilon^2} \log n)$ and majority-bias of $\Omega(\sqrt{\log n/|A|})$. To solve this problem, we first set:

$$i_A := \frac{\log(|A|/\log n)}{2 \log(1/\epsilon)},$$

and then execute phases $i_A, i_{A+1} \dots T + 1$ of stage 1, and subsequently execute stage 2. \square

3 Removing the global clock assumption

In this section we show how to remove the assumption that all clocks are initialized to 0 at the beginning of the execution. The removal of this assumption will yield an additive increase of $O(\log^2 n)$ in the running time, while preserving the optimal $O(\frac{1}{\epsilon^2} n \log n)$ message complexity.

Before completely removing the assumption of a global clock, let us first consider a relaxed version of it where it is guaranteed that at the beginning of the execution, each clock is initialized to some integer in the range $[0, D)$, for a given D . (In particular, any two clocks are at most D apart.) Recall that the algorithm mentioned in Section 2 for the fully-synchronous setting, considers $O(\log n)$ consecutive phases, where phase i takes place during the time period $[r_i, r_i + x_i)$, for some integers r_i and x_i (here x_i is the length of phase i , and we have $r_{i+1} = r_i + x_i$). In Section 2, assuming the global clock assumption, it is guaranteed that all agents execute the same phase at the same time. We now modify that algorithm to fit to the relax setting where all clocks are in the range $[0, D)$.

In the modified algorithm, each agent will execute phase i as described in Section 2, except that instead of starting it at time r_i it will start it when its own clock shows $r_i + iD$. That is, Agent a will execute phase i during the time interval when its own clock shows $[r_i + iD, r_i + iD + x_i)$. Let s (respectively, ℓ) be the smallest (and respectively, the largest) value in $[0, D)$ such that an agent started the execution with this time on its clock. For the sake of the analysis, assume we start the execution at the *global* time 0 (in this time, all local clocks are in the range $[0, D)$). Each agent a will start phase i at some global time, not before the time $s + r_i + iD \geq r_i + iD$, and will end it before time $\ell + r_i + iD + x_i < r_{i+1} + (i + 1)D$. Hence, all agents will execute phase i during the global time interval $[r_i + iD, r_{i+1} + (i + 1)D)$. (Note that these intervals are disjoint for different values of i). This is sufficient to guarantee that the modified algorithm is correct. Since the number of phases is $O(\log n)$, we immediately have that the increase in number of rounds is an additive term of $O(D \log n)$ rounds. (Note, the message complexity remains the same as in the fully-synchronous case, since we only add waiting rounds over the original fully-synchronous algorithm).

We now claim that if D is initially unbounded, we can easily (and quickly) reduce it to $D = 3 \log n$, by first performing an *activation* phase, in which each informed agent broadcasts an arbitrary message for $\log n$ rounds, and setting the clock of an agent to be 0 after D rounds passed since it heard a message for the first time. W.h.p., after $3 \log n$ rounds all agents have been activated, ensuring that when the clocks are initialized again, all clocks are at most $3 \log n$ apart. Applying the aforementioned algorithm for the case $D := 3 \log n$ establishes the following.

Theorem 3.1. *Consider the synchronous setting. There exists algorithms solving the noisy rumor-spreading problem and the noisy majority-consensus problem (with an initial set of agents A of size $|A| = \Omega(\frac{1}{\epsilon^2} \log n)$ and majority-bias of $\Omega(\sqrt{\log n / |A|})$). Both these algorithms terminate in $O(\frac{1}{\epsilon^2} \log n + \log^2 n)$ rounds, and use $O(\frac{1}{\epsilon^2} n \log n)$ messages.*

The term $O(\log^2 n)$ added to the running time in both algorithms in Theorem 3.1 can be reduced if agents could quickly synchronize their clocks by a smaller factor than $O(\log n)$. Optimizing this clock-gap between agents remains an intriguing question of independent interest.

4 Discussion

We have presented the Flip model, a basic model of communication wherein interactions are conveyed across noisy channels of limited capacity. This noisy communication can be expected to capture an important aspect of naturally occurring, biological interactions that is overlooked by the classical fault-tolerance models studied in distribute computing. We have then presented robust and simple algorithms that efficiently solve two basic information dissemination problems within the model's constraints. Besides the purely theoretical interest, we believe that the protocols presented in this paper provide valuable insights towards the understanding of communication schemes in nature. Indeed, our algorithms suggest balancing between silence and transmission, synchronization, and majority-based decisions as important ingredients towards understanding collective behavior in anonymous and noisy natural populations.

As this is a first attempt at analyzing randomly distorted messages with distributed computing tools, we did not attempt to describe a specific biological system or identify naturally occurring algorithms. Rather,

our results indicate that to understand natural systems one must simultaneously consider communication noise, limited messaging alphabet, and algorithm. Typically, works in different fields take only subset of these three components into account.

Acknowledgments: The authors would like to thank Oded Goldreich, Kunal Talwar, James Aspnes, and George Giakkoupis for helpful discussions.

References

- [1] Yehuda Afek, Noga Alon, Omer Barad, Eran Hornstein, Naama Barkai, and Ziv Bar-Joseph. *A biological solution to a fundamental distributed computing problem*. Science 331:6014, 183–5, (2011).
- [2] Yehuda Afek, Noga Alon, Ziv Bar-Joseph, Alejandro Cornejo, Bernhard Haeupler, Fabian Kuhn. *Beeping a maximal independent set*. Distributed Computing 26(4), 195–208, (2013).
- [3] Christina Allen and Charles Stevens. *An evaluation of causes for unreliability of synaptic transmission*. Proceedings of the National Academy of Sciences 91, 10380–10383, (1994).
- [4] Dana Angluin, James Aspnes, Zoë Diamadi, Michael J. Fischer, René Peralta. *Computation in networks of passively mobile finite-state sensors*. Distributed Computing 18(4), 235–253, (2006).
- [5] Dana Angluin, James Aspnes, Michael J. Fischer, and Hong Jiang. *Self-stabilizing population protocols*. TAAS 3(4), (2008).
- [6] Dana Angluin, James Aspnes, and David Eisenstat. *A simple population protocol for fast robust approximate majority*. Distributed Computing 21(2), 87–102, (2008).
- [7] James Aspnes and Eric Ruppert. *An Introduction to Population Protocols*. Bulletin of the EATCS 93, 98–117, (2007).
- [8] Bonnie L. Bassler and Christopher M. Waters. *Quorum Sensing: Cell-to-Cell Communication in Bacteria*. The Annual Review of Cell and Developmental Biology 21, 319–346, (2005).
- [9] Reuven Bar-Yehuda and Shay Kutten. *Fault Tolerant Distributed Majority Commitment*. J. Algorithms 9(4), 568–582 (1988).
- [10] Joffroy Beauquier, Janna Burman, and Shay Kutten. *Making Population Protocols Self-stabilizing*. SSS 2009: 90–104.
- [11] Ohad Ben-Shahar, Shlomi Dolev, Andrey Dolgin, and Michael Segal. *Direction election in flocking swarms*. Ad Hoc Networks 12, 250–258 (2014)
- [12] John Buck. *Synchronous Rhythmic Flashing of Fireflies. II*. The Quarterly Review of Biology 63(3), 265–289, (1988).
- [13] Henrik Brumm and Hans Slabbekoorn. *Acoustic Communication in Noise*. Advances in the Study of Behavior 35, 151–209, (2005).
- [14] Michael C. Carrol. *The complement system in regulation of adaptive immunity*. Nature Immunology 5, 981–986, (2004).
- [15] Keren Censor-Hillel, Bernhard Haeupler, Jonathan A. Kelner, and Petar Maymounkov. *Global computation in a poorly connected world: fast rumor-spreading with no dependence on conductance*. Proc. of the ACM Symposium on Theory of Computing (STOC), 961–970, (2012).
- [16] Bernard Chazelle. *Natural algorithms*. Proc. of the ACM-SIAM Symposium on Discrete Algorithms (SODA), 422–431, (2009).
- [17] Alan J. Demers, Daniel H. Greene, Carl Hauser, Wes Irish, John Larson, Scott Shenker, Howard E. Sturgis, Daniel C. Swinehart, and Douglas B. Terry. *Epidemic algorithms for replicated database maintenance*. Operating Systems Review 22 no. 1, 8–32, (1988).

- [18] Krzysztof Diks and Andrzej Pelc. *Optimal adaptive broadcasting with a bounded fraction of faulty nodes*. *Algorithmica* 28 no. 1, 37–50, (2000).
- [19] Benjamin Doerr and Mahmoud Fouz. *Asymptotically optimal rumor-spreading*. *Proc. of the International Colloquium on Automata, Languages, and Programming (ICALP)*, 502–513, (2011).
- [20] Robert Elsässer and Thomas Sauerwald. *On the runtime and robustness of randomized broadcasting*. *Theoretical Computer Science* 410 no. 36, 3414–3427, (2009).
- [21] Yuval Emek and Roger Wattenhofer. *Stone age distributed computing*. *Proc. of the ACM SIGACT-SIGOPS Symposium on Principles of Distributed Computing (PODC)*, 137–146, (2013).
- [22] Ofer Feinerman, Joel Veiga, Jeffrey Dorfman, Ronald Germain, and Gregoire Altan-Bonnet. *Variability and robustness in T cell activation from regulated heterogeneity in protein levels*. *Science* 321(5892), 1081–1084, (2008).
- [23] Ofer Feinerman, Garrit Jentsch, Karen Tkach, Jesse Coward, Matthew Hathorn, Michael Sneddon, Thierry Emonet, Kendall Smith, and Gregoire Altan-Bonnet. *Single-cell quantification of IL-2 response by effector and regulatory T cells reveals critical plasticity in immune response..* *Molecular systems biology* 6, 437pp, (2010).
- [24] Pierre Fraigniaud, and George Giakkoupis. *On the bit communication complexity of randomized rumor-spreading*. *Proc. of the ACM Symposium on Parallelism in Algorithms and Architectures (SPAA)*, 134–143, (2010).
- [25] Nigel R Franks, Stephen C Pratt, Eamonn B Mallon, Nicholas F Britton and David JT Sumpter. *Information flow, opinion polling and collective intelligence in househunting social insects*. *The Royal Society B* 537(1427), 1567–1583, (2002).
- [26] Alan M. Frieze and Geoffrey R. Grimmett. *The shortest-path problem for graphs with random arc-lengths* *Discrete Applied Mathematics* 10, 57–77, (1985).
- [27] Abbas El Gamal and Young-Han Kim. *Network Information Theory*. Cambridge University Press, 709pp, (2012).
- [28] Chryssis Georgiou, Seth Gilbert, and Dariusz R. Kowalski. *Meeting the deadline: on the complexity of fault-tolerant continuous gossip*. *Distributed Computing* 24(5), 223–244 (2011).
- [29] Chryssis Georgiou, Seth Gilbert, Rachid Guerraoui, and Dariusz R. Kowalski. *Asynchronous gossip*. *J. ACM* 60(2), 11 (2013).
- [30] Leszek Gasieniec and Andrzej Pelc. *Adaptive broadcasting with faulty nodes*. *Parallel Computing* 22 no. 6, 903–912, (1996).
- [31] George Giakkoupis and Thomas Sauerwald. *rumor-spreading and vertex expansion*. *Proc. of the ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 1623–1641, (2012).
- [32] Bernhard Haeupler. *Analyzing Network Coding Gossip Made Easy*. *Proc. of the ACM Symposium on Theory of Computing (STOC)*, 293–302, (2011).
- [33] Bernhard Haeupler. *Simple, Fast, and Deterministic Gossip and rumor-spreading*. *Proc. of the ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 705–716, (2013).
- [34] Yuji Ikegaya, Gloster Aaron, Rosa Cossart, Dmitriy Aronov, Ilan Lampl, David Ferster, and Rafael Yuste. *Synfire Chains and Cortical Songs: Temporal Modules of Cortical Activity*. *Science* 304(5670), 559–564, (2004).
- [35] Soumya Kar and Jose MF Moura. *Distributed Consensus Algorithms in Sensor Networks With Imperfect Communication: Link Failures and Channel Noise* *IEEE Transactions on Signal Processing* 57(1), 355–369, (2009).
- [36] Richard M. Karp, Christian Schindelhauer, Scott Shenker, and Berthold Vöcking. *Randomized rumor-spreading*. *Proc. of the IEEE Symposium on Foundations of Computer Science (FOCS)*, 565–574, (2000)
- [37] Ralf Koetter and Frank R. Kschischang. *Coding for errors and erasures in random network coding*. *IEEE Transactions on Information Theory* 54 no. 8, 3579–3591, (2008)

- [38] Thierry Lengagne, Thierry Aubin, Jacques Lauga, and Pierre J. Jouventin. *How do king penguins (*Aptenodytes patagonicus*) apply the mathematical theory of information to communicate in windy conditions?* Proc. of the Royal Society B: Biological Sciences 266(1429), 1623–1628, (1999).
- [39] George B. Mertzios, Sotiris E. Nikolettseas, Christoforos Raptopoulos, and Paul G. Spirakis. *Natural models for evolution on networks*. Theor. Comput. Sci. 477, 76–95 (2013).
- [40] Othon Michail, Ioannis Chatzigiannakis, and Paul G. Spirakis. *Mediated population protocols*. Theor. Comput. Sci. 412(22), 2434–2450 (2011).
- [41] Mauro Mobilia, A. Petersen, and Sidney Redner. *Spread of epidemic disease on networks*. Physical Review E 66(16128), (2002).
- [42] Mauro Mobilia. *Does A Single Zealot Affect an Infinite Group of Voters* Physical Review Letters 91(028701), (2003)
- [43] Mauro Mobilia, A. Petersen, and Sidney Redner. *On the role of zealotry in the voter model*. Journal of Statistical Mechanics, P08029, (2007).
- [44] Todd Moon. *Error Correction Coding: Mathematical Methods and Algorithms*. Wiley-Interscience, 800pp, (2005).
- [45] David Peleg. *Distributed Computing: A Locality-Sensitive Approach*. SIAM, (2000).
- [46] Boris Pittel. *On spreading a rumor*. SIAM Journal on Applied Mathematics 47 no. 1, 213–223, (1987).
- [47] Nitzan Razin, Jean-pierre Eckmann, and Ofer Feinerman. *Desert ants achieve reliable recruitment across noisy interactions*. Journal of the Royal Society Interface 10(20130079), (2013).
- [48] Gilbert Roberts. *Why individual vigilance increases as group size increases*. Animal Behaviour 51, 1077–1086, (1996).
- [49] Claude Shannon. *A Mathematical Theory of Communication*. Bell System Technical Journal 27(3), 379–423, (1948).
- [50] David JT Sumpter, Jens Krause, Richard James, Iain D. Couzin, and Ashley JW Ward. *Consensus Decision Making by Fish*. Current Biology 22(25), 1773–1777, (2008).
- [51] Yuri Sykulev, Michael Joo, Irina Vturina, Theodore J. Tsomides, and Herman N Eisen. *Evidence that a Single Peptide-MHC Complex on a Target Cell Can Elicit a Cytolytic T Cell Response*. Immunity 4(6), 565–571, (1996).
- [52] Edward O. Wilson and Bert Holldobler. *The Superorganism: The Beauty, Elegance, and Strangeness of Insect Societies*. W. W. Norton & Company, 544pp, (2008).