

# Determining the Mobility of Ions in Perovskite Solar Cells – Measurement and Simulation

Evelyne Knapp<sup>a</sup>, Martin Neukom<sup>a,b</sup>, Stéphane Altazin<sup>b</sup>, Simon Züfle<sup>a,b</sup>, Beat Ruhstaller<sup>a,b</sup>

a Institute of Computational Physics, ZHAW, 8401 Winterthur, Switzerland

b Fluxim AG, 8406 Winterthur, Switzerland

The evidence is compelling that mobile ions are responsible for the IV-curve hysteresis observed in perovskite solar cells. Calculations show that iodine and methylammonium (MA) vacancies are indeed mobile within the perovskite crystal. The calculations predict a diffusion coefficient for both types of vacancies [1, 2]. Cell simulations incorporating mobile ions confirm the scan-rate dependent occurrence of an IV-curve hysteresis [3, 4, 5]. In order to elucidate the dynamics of electronic and ionic charges in the perovskite cells we acquire current responses to a voltage-step in the dark in a large range of time scales from microseconds to seconds. The measurement results are compared with simulations that employ a fully-coupled drift-diffusion solver incorporating mobile ions. We explain distinct features of the current-rise and how they are attributed to motion of mobile ions within the bulk. The delay time between voltage step and current-rise is used to estimate the ion mobility. We furthermore show evidence that a second ion type is mobile with a much lower mobility, presumably MA vacancies. Moreover, it is observed that the extracted ion mobilities depend on the fabrication type (evaporated versus solution-processed). Shao and co-workers presented evidence that ion migration is dominant in grain boundaries [6]. Thus, different grain-size and grain-boundaries might be the origin of the variation in ion mobility of the perovskite devices produced with different processing conditions. We conclude that transient currents acquired over a broad range of time scales combined with numerical device simulation represent a powerful method to study electronic and ionic charge transport properties.

## References:

- [1] Eames, Christopher, Jarvist M. Frost, Piers R. F. Barnes, Brian C. O'Regan, Aron Walsh, and M. Saiful Islam. *Nature Communications* 6 (June 24, 2015)
- [2] Walsh, Aron, David O. Scanlon, Shiyu Chen, X. G. Gong, and Su-Huai Wei. *Angewandte Chemie International Edition* 54, no. 6 (February 2, 2015): 1791–94. doi:10.1002/anie.201409740.
- [3] Richardson, Giles, Simon E. J. O'Kane, Ralf G. Niemann, Timo A. Peltola, Jamie M. Foster, Petra J. Cameron, and Alison B. Walker. *Energy Environ. Sci.*, 2016. doi:10.1039/C5EE02740C.
- [4] Reenen, Stephan van, Martijn Kemerink, and Henry J. Snaith. *The Journal of Physical Chemistry Letters*, September 10, 2015, 3808–14. doi:10.1021/acs.jpcllett.5b01645.
- [5] Calado, Philip, Andrew M. Telford, Daniel Bryant, Xiaoe Li, Jenny Nelson, Brian C. O'Regan, and Piers R.F. Barnes. *Nature Communications* 7 (December 22, 2016): 13831. doi:10.1038/ncomms13831.
- [6] Shao, Yuchuan, Yanjun Fang, Tao Li, Qi Wang, Qingfeng Dong, Yehao Deng, Yongbo Yuan, et al. *Energy Environ. Sci.* 9, no. 5 (2016): 1752–59. doi:10.1039/C6EE00413J.